



POWERFUL COMPACT DURABLE EASY-TO-USE RELIABLE

THE CARPET RESTORATION SOLUTION

This is why you need a Rush Extractor:

- Powerful cleaning performace with features like dual vacuums for optimum recovery and up to 500 psi all in a compact, easy to use design
- Unique external heater boosts cleaning performance, protects internal electrical components, and eliminates downtime
- Simple two screw access to components for easy maintenance and service
- Wand and hoses included in the package

Increase your productivity on those tough carpet restoration jobs with the NEW Rush portable extractors.



RUSH SERIES PORTABLE HEATED CARPET EXTRACTORS

Rush Series Features & Specifications

- Heat-ready extractors offer the ultimate in cleaning performance
- The external heater is easily installed or removed for easy maintenance, and keeps heat away from the motor compartment
- Upright-mounted motors along with a special intercooler guarantee long life and durability
- Standard 5-gallon bucket fits under drain valve for easy emptying
- · Easily opens with two screws for easy servicing
- Easy access top-mounted switches
- Sealed motor cavity protects electronics from water damage
- Convenient back mounted components make it easy to maneuver the machine out of the way while cleaning
- Large rear wheels protect all the components from damage during transport
- 3 sides are totally free of fittings so it's easy to load without damage on either side, the front or on its wheels with the casters locked
- Twist lock cord allows you to drop the cord in place and wheel the machine to a drain or toilet to fill or empty

| Models | Rush 100 Cold | Rush 100 | Rush 500 |
|---------------------------|-----------------------------------|-----------------------------------|------------------------------------|
| Solution Tank | 12 gallon | 12 gallon | 12 gallon |
| Recovery Tank | 11 gallon | 11 gallon | 11 gallon |
| Vacuum Motors | Dual 2-stage | Single 3-stage | Dual 2-stage |
| Solution Pressure | 100 psi | 100 psi | 500 psi |
| Water Lift | 150" | 117" | 150" |
| Tank Construction | Polyethylene | Polyethylene | Polyethylene |
| Baseplate | ¼" aluminum | ¼" aluminum | ¼" aluminum |
| Rear Wheels | 10" non-marking | 10" non-marking | 10" non-marking |
| Casters | 4" locking | 4" locking | 4" locking |
| Power Cord | 50 ft. detachable | 50 ft. detachable | Dual 50 ft. de- tachable |
| Dimensions | 35"H x 31"L x 18"W | 35"H x 31"L x 18"W | 35"H x 31"L x 18"W |
| Weight | 78 lbs. | 90 lbs. | 106 lbs. |
| Shipping Weight | 94 lbs. | 106 lbs. | 123 lbs. |
| Shipping Dimensions | 36.5"H x 31.5"L x 19"W | 36.5"H x 31.5"L x 19"W | 36.5"H x 31.5"L x 19"W |
| Electrical Draw | 13.5 amps | 18.8 amps | 17.1 amps/15.9 amps |
| Heater | No Heat | Detachable – 1000 W | Detachable – 2000 W |
| Vacuum/Solu- tion Hose | 15′ | 15′ | 25′ |
| Carpet Wand | Single Jet – Stain- less Steel | Single Jet – Stain- less Steel | Dual Jet/S-bend Stainless Steel |

