





X17 SERIES SELF-CONTAINED CARPET EXTRACTORS

X17 Series Features & Specifications







Key Features:

- Constructed of non-corrosive polyethylene that won't dent, corrode or rust
- Two quick disconnect spray jets allow for simple maintenance
- · Automatic float shutoff prevents damage to the vacuum motor
- · Single, adjustable brush runs at 1800 RPM
- CRI Certified for proven cleaning performance
- Large 9 or 11 gallon solution tank and 7.5 gallon recovery tank
- On-board power for optional scrub wand and extraction tools
- Faucet-fill function offers convenient filling of the solution tank
- Removable recovery tank has convenient dump hose that saves time and empties easily
- Adjustable handle fits to the size of the operator

CFS From Minuteman

The patented CFS (Chemical Free Solution) system requires Zero chemical or disinfectants. The CFS equipped machines use Ozone to sanitize, deodorize and purify soft floors using an innovative Ozone technology that's revolutionizing the way we clean carpets.

Sanitize - Ozone kills pathogens more broadly than chlorine or other chemical sanitizers **Deodorize** - Ozone is one of the most powerful deodorizers known

Purify - Ozone destroys residual pesticides in water and on the surface of carpet and breaks down trace pharmaceuticals (e.g. estrogen) in water

Conserve - Ozone creates fewer by-products than chemical sanitizers and uses less energy than sanitizing with heat

| | • | | | |
|------------------------|---|---|---|---|
| Models | X17/X17 HP | X17 CFS | X17 Plus/ Plus HP | X17 Plus CFS |
| Cleaning Path Width | 17" (43 cm) | 17" (43 cm) | 17" (43 cm) | 17" (43 cm) |
| Solution Tank | 9 gallon (34 lt.) | 9 gallon (34 lt.) | 11 gallon (42 lt.) | 11 gallon (42 lt.) |
| Recovery Tank | 7.5 gallon (28.4 lt.) | 7.5 gallon (28.4 lt.) | 10 gallon (37.9 lt.) | 10 gallon (37.9 lt.) |
| Vacuum Motors | 2 HP 3-stage | 2 HP 3-stage | 2 HP 3-stage | 2 HP 3-stage |
| Solution Pressure | 50 psi / 100 psi | 50 psi | 50 psi / 100 psi | 50 psi |
| Brush Motor | 1/6 HP | 1/6 HP | 1/6 HP | 1/6 HP |
| Tank Construction | Polyethylene | Polyethylene | Polyethylene | Polyethylene |
| Rated Voltage | Available in 115V and 230V |
| Rear Wheels | 10" non-mark- ing | 10" non-mark- ing | 10" non-marking | 10" non-marking |
| Waterlift | 118" | 118" | 118" | 118" |
| Power Cord | 50 ft. | 50 ft. | 50 ft. | 50 ft. |
| Brush Speed | 1800 RPM | 1800 RPM | 1800 RPM | 1800 RPM |
| CFM | 99 | 99 | 99 | 99 |
| Spray Jets | Dual jet | Dual jet | Dual jet | Dual jet |
| Options | Scrub wand, ET tool, 15' vac hose |