



**Gotcha!<sup>®</sup> Carpet Spotter**  
Portable Carpet Spotter



## General Overview

- The Gotcha! is designed for spot removal and carpet maintenance operations that require maneuverability, efficiency, power and hassle-free, one-person operation
- Lightweight machine is portable for quick and efficient spot removal

## Productivity

- 1.12 hp vac motor creates 71" waterlift/80CFM
- Recovers more soil and dirty solution faster to shorten drying time
- Quick and efficient solution for spot and stain removal without needing to use bulky equipment

## Ease of Use

- Compact and lightweight can be rolled on 4" wheels or carried via the built in strap or handle
- Easy-to-use two-position switch allows user to choose from vacuum only mode or dual action vacuum/pump mode
- Solution tank detaches for easy disposal of dirty water

## Key Features

- Large 2 gallon solution/recovery tanks allow for cleaning multiple spots before refilling
- 4" clear handle allows the operator to see soil and residue being extracted
- Heavy-duty Viton™ seals are impervious the chemicals available today

## Safety

- Ground fault circuit interrupter shuts off machine in the event of an electrically hazardous situation protecting the operator from electric shock

## Markets

- Hospitality
- Institutional
- Health care
- Building service contractors
- Airports
- Retail

## Accessories/Options

- ET extraction tool
- Transport Cart, Chemical Spotting Kit, Gotcha! Shampoo

| Specifications                         |                                                          |
|----------------------------------------|----------------------------------------------------------|
| <b>Solution/Recovery Tank Capacity</b> | 2.0 gallons (7.6 ltr)                                    |
| <b>Voltage</b>                         | 115 volts / 240 volts                                    |
| <b>Vacuum Motor</b>                    | 1.12 hp, 2 stage                                         |
| <b>Waterlift</b>                       | 71" (1,800 mm)                                           |
| <b>Air Flow</b>                        | 80 CFM (2.5m <sup>3</sup> per min)                       |
| <b>Solution Pump</b>                   | 50 PSI                                                   |
| <b>Cable</b>                           | 25' (8m), 18-3 wire with GFCI (Ground Fault Interrupter) |
| <b>Construction</b>                    | Rotationally Molded Polyethylene                         |
| <b>Hand Tool</b>                       | 4" (10 cm) width, clear Injection - molded construction  |
| <b>Solution/Vacuum Hose</b>            | 8' (2.4 M)                                               |
| <b>Switch</b>                          | 2 position (vacuum only and vacuum/pump)                 |
| <b>Dimensions (LxWxH)</b>              | 19" x 8.75" x 17"<br>(48 cm x 22 cm x 43 cm)             |
| <b>Weight</b>                          | 19 lbs (8.6 kg)                                          |
| <b>Wheel Diameter</b>                  | (2) - 4" (10 cm)                                         |

Specifications are subject to change without notice.